



Formula ID 1578 Compound XP-5756-B Cure: P Color: B
Urethane Type: Polyester

Application: 80 Shore A, Black, Anti-Static Millathane® 66/66R Compound

Millathane® 66/66R Premilled	101.50	Durometer, Shore A	80	
Stearic Acid	0.20	Durometer, Shore D		
N330 Black	40.00	Durometer, Asker C		
DBEEA (TP-95)	5.00	25% Modulus, psi		MPa
Struktol WB-222	1.00	50% Modulus, psi		MPa
AC617A Polyethylene	1.00	100% Modulus, psi	830	5.7 MPa
SR 517	10.00	200% Modulus, psi	1980	13.7 MPa
SR 231 (DEGDMA)	5.00	300% Modulus, psi	3080	21.2 MPa
Varox DBPH-50	6.00	Tensile Strength, psi	3430	23.7 MPa
		Elongation, %	353	
		Tear Die C, lb/in.	209	36.6 kN/m
		Tear Die B, lb/in.		kN/m
		Tear Die T, lb/in.		kN/m
		Specific Gravity, g/cc	1.260	
		CureTime, minutes	8	
		Cure Temp°F	338	170 °C
		Mooney Viscosity, ML4/100°C	33	
		Heat Aging <input type="text"/> Hrs at <input type="text"/> °C		
		Hardness Change, pts.		
		Tensile Change, %		
		Elongation Change, %		
		Fluid Aging <input type="text"/> Hrs at <input type="text"/> °C		
		Hardness Change, pts.		
		Tensile Change, %		
		Elongation Change, %		
		Volume Change, %		
		Surface Resistivity, ohm/cm ²	5.0E+08	
		Volume Resistivity, ohm-cm		
		UL 94 Rating:		
		Compression Set, Other conditions:		
		<input type="text"/> h/ <input type="text"/> °C, %		
		Compression Set 22h/70°C, %	9	
		Compression Set 70h/70°C, %		
		Compression Set 22h/100°C, %		
		Compression Set 70h/100°C, %		
		Compression Set 22h/125°C, %		
		Compression Set 22h/150°C, %		
		Total	169.70	

Other Tests and Info:

Resistivity tester only measures powers of 10, so the "5.0" of the surface resistivity is estimated. SR-517 is a scorch-retarded trifunctional methacrylate from Sartomer

10/1/2020

The recommendations for the use of our products are based on tests believed to be reliable. However, we do not guarantee the results to be obtained by others under different conditions nor do we guarantee that this or other formulas will work in a specific application. Nothing in this literature is intended as a recommendation to use our products so as to infringe on any patent. Millstab™ is a trademark, and Millathane® and Thanecure® are registered trademarks of TSE Industries, Inc. All other brand names and product names referenced are trademarks, registered trademarks or trade names of their respective holders.